

IN THE WRITTEN DESCRIPTION

Replace the paragraph beginning on page 1 line 3 with:

This application is a Continuation of U.S. Patent Application No. 09/641,758 filed August 21, 2000, now U.S. Patent No. 6,458,046, which is incorporated herein by reference in its entirety.

Replace the paragraph beginning on page 37 line 3 (the Abstract) with:

B1

A multi-layer golf ball can be prepared, possessing the performance characteristics of both a solid ball and a wound ball, by selecting the content and thickness of one or more of the layers, wherein the multi-layer golf ball comprises a center, an intermediate layer, a wound layer of tensioned material, and a cover, such that any one or more of the following are satisfied: (a) at least a portion of the intermediate layer includes a thermoset material; (b) the winding includes fiber, glass, carbon, polyether urea, polyether block copolymers, polyester urea, polyester block copolymers, isotactic-poly(propylene), polyethylene, polyamide, poly(oxymethyiene), polyketone, poly(ethylene terephthalate), poly(p-phenylene terephthalamide), poly(acrylonitrile), diaminodicyclohexylnethane, dodecanedicarboxylic acid, or copolymers or combinations thereof; (c) the thickness of the wound layer is less than about ± 1 mm; and (d) at least a portion of the cover includes a thermoset material.

Methods of preparation of such golf balls are also recited.